

Submittal Data Sheet

absolute comfort

Performance

Indoor Unit Model No:	Ducted
Outdoor Unit Model No:	REYQ120PATJ
Cooling Capacity (Btu/hr):	114000
Sensible Capacity (Btu/hr):	0
Cooling Input Power (kW):	
Cooling EER (Btu/hr / kW):	11.0
SEER:	N/A
Heating Capacity (Btu/hr):	130000
Heating Input Power (kW):	
Heating COP (Btu/hr / Btu/hr):	3.3
HSPF:	N/A

Approval:	
Date:	
Construction:	
Unit #:	
Drawing #:	

Indoor Unit Type:	
Condensing Unit Type:	10-Ton VRV-III Heat Recovery
Cooling Nominal Conditions	Indoor: 80°F DB/67°F WB
	Outdoor: 95°F DB/75°F WB
	Water Cooled:
Heating Nominal Conditions	Indoor: 47°F DB/43°F WB
	Outdoor: 47°F DB/43°F WB
	Water Cooled:
Nominal Piping Length	25
Nominal Height Separation	0
Nominal Water Flow Rate	

Indoor Unit Details

Power Supply (V/Hz/Ph:)	N/A
Power Supply Connections:	
Min. Circuit Amps MCA (A):	
Max. Fusible Amps MFA (A):	
Dimensions (HxWxD):	N/A
Panel (HxWxD):	N/A
Net Weight (lbs):	
Weight with Panel (lbs):	

Condensing Unit Details

Power Supply (V/Hz/Ph):	208-230/60/3ph
Power Supply Connections:	L1, L2, L3 Ground
Min. Circuit Amps MCA (A):	44.2
Max. Fusible Amps MFA (A):	50
Max. Starting Current MSC(A):	131
Rated Load Amps RLA (A):	12.0+13.6
Total Overcurrent Amps (A):	54.3
Dimensions (HxWxD):	66-1/8x51-3/16x30-1/8
Net Weight (lbs):	730
Compressor Type:	Inverter
Capacity Control Range (%):	14 - 100
Capacity Index Limit:	72 - 156 (130%)

System Details

Refrigerant Type:	R-410A
Holding Refrigerant Charge (lbs):	23.8
Additional Charge (oz/ft):	install data
Pre-charge Piping (Length ft):	-
Max. Pipe Length (Total ft):	540 ft
Max. Pipe Length (Vertical ft):	164 ft (295 ft) / 295 ft

Airflow Rate (CFM wet coil)	N/A
Moisture Removal (pt/h):	
Gas Pipe Connection (inch):	
Liquid Pipe Connection (inch):	
Condensate Connection (inch):	
Sound Pressure Level (dBA):	
Sound Power Level (dBA):	
Nominal External Static Pressure (inH2O)	
Max Ext Static Pressure (inH2O)	

Airflow Rate (CFM):	7410
Gas Pipe Connection (inch):	1-1/8
Liquid Pipe Connection (inch):	1/2
H/L Pressure Connection (inch):	3/4
H/L Equalizing Connection (inch):	
Water Inlet Connection (inch FPT):	
Water Outlet Connection (inch FPT):	
Condensate Drain Outlet (inch FPS):	
Sound Pressure Level (dBA):	60
Sound Power Level (dBA):	
Unit Heat Rejection (kW):	
Max. No. of Indoor Units:	20

Cooling Operation Range (°F):	(-4) 23 - 122
Cooling Range w/Baffle (°F):	
Heating Operation Range (°F):	0 - 77 / -4 - 60
Heating Range w/Baffle (°F):	
Cooling Inlet Water Temp (°F):	
Heating Inlet Water Temp (°F):	
Water Flow Range (GPM):	

Daikin AC (Americas), Inc., 1645 Wallace Drive - Suite 110, Carrollton, TX 75006

Daikin AC TRL Generated Submittal Data



Project Name:		
Location:	Approval:	
Engineer:	Date:	
Submitted to:	Construction:	
Submitted by:	Unit #:	
Reference:	Drawing #:	






Submittal Data Sheet

Approval:	
Date:	
Construction:	
Jnit #:	
Drawing #:	

Dimensional Drawing - Condensing Unit

Daikin AC TRL Generated Submittal Data





Submittal Data Sheet

Project Name:	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

<u>Notes</u>

Daikin AC TRL Generated Submittal Data

Std U.S. Warranty: 6yrs Compressor, 1yrs Parts, 1yr Limited Labor

Daikin AC (Americas), Inc., 1645 Wallace Drive - Suite 110, Carrollton, TX 75006