

Job Name: \_\_\_\_\_

Purchaser: \_\_\_\_\_

Submitted To: \_\_\_\_\_

Submitted By: \_\_\_\_\_

Unit Designation: \_\_\_\_\_

Location: \_\_\_\_\_

Engineer: \_\_\_\_\_

For:  Reference  Approval  Construction

Date: \_\_\_\_\_

**Technical Specification:**

**Features:**

Heating only	Yes
Heating and Cooling	Yes
Comfort function mode	Yes
Reduced function mode	Yes
Number of setpoint changes	12/day
Holiday function	Yes
Off function	Yes
Setpoint limitation	Yes
Keylock function	Yes
Clock	Yes
Regulation function	Proportional band

**Temperature Setting range:**

Operation	32~122°F (0~50°C)
Heating	39.2~98.6°F (4~37°C)
Cooling	39.2~98.6°F (4~37°C)

**Ambient temperature:**

Storage	-4~140°F (-20~60°C)
---------	---------------------

**Dimensions:**



Unit (HxWxD)	3-1/2" x 5" x 1-3/8"
Unit weight	7.6 oz

**Standard Features:**

Parts warranty	5 years
Limited labor warranty	1 year

**Electrical Specification:**

Unit power supply	Battery 3*AA - LR6(alkaline)
Connection	Wired
Output relays	Maximum load 1A - 24VAC



H	Heating demand
C	Cooling demand

For heating-only applications, wire 2-C is not to be installed.

For further information about the installation, please refer to the Installation and Engineering Guides