

Project Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_

### Performance

*Indoor Unit Model No:* FTXN09KEVJU  
*Outdoor Unit Model No:* RXN09KEVJU  
*Rated Cooling Capacity (Btu/hr):* 9000  
*Sensible Capacity (Btu/hr):* 5600  
*Max/Min Cooling Capacity (Btu/hr / kW):* 9500/4400  
*Cooling Input Power (kW):* 0.79  
*SEER:* 18  
*Rated Heating Capacity (Btu/hr):* 10000  
*Max/Min Heating Capacity (Btu/hr / kW):* 11600/4400  
*Heating Input Power (kW):* 0.84  
*Heating COP (Btu/hr / Btu/hr):* 3.49  
*HSPF:* 8.5

*Indoor Unit Type:* Wall Mounted  
*Condensing Unit Type:* Std SEER Heat Pump  
*Rated Cooling Conditions*  
 Indoor: 80°F DB/67°F WB  
 Outdoor: 95°F DB/75°F WB  
*Rated Heating Conditions*  
 Indoor: 70°F DB/60°F WB  
 Outdoor: 47°F DB/43°F WB  
*Rated Piping Length(ft)* 25  
*Rated Height Separation(ft)* 0

### Indoor Unit Details

*Power Supply (V/Hz/Ph):* 208-230/60/1ph  
*Power Supply Connections:* L1, L2, Ground  
*Min Circuit Amps MCA (A):* N/A  
*Max Overcurrent Amps MFA (A):* N/A  
*Dimensions (HxWxD):* 11-1/8x30-1/4x7-3/4  
*Panel (HxWxD):* N/A  
*Net Weight (lbs):* 16  
*Weight with Panel (lbs):* \_\_\_\_\_

*Airflow Rate (CFM wet coil)* 325/244/162  
*Moisture Removal (pt/h):* \_\_\_\_\_  
*Gas Pipe Connection (inch):* 3/8  
*Liquid Pipe Connection (inch):* 1/4  
*Condensate Connection (inch):* 5/8  
*Sound Pressure Level (dBA):* 40  
*Sound Power Level (dBA):* 56  
*Static Pressure Rated/Max (inWg)* 0 / 0/0

### Condensing Unit Details

*Power Supply (V/Hz/Ph):* 208-230/60/1ph  
*Power Supply Connections:* L1, L2, Ground  
*Min. Circuit Amps MCA (A):* 4.8  
*Max. Overcurrent Amps MFA (A):* 15  
*Max. Starting Current MSC(A):* \_\_\_\_\_  
*Rated Load Amps RLA (A):* 4.1  
*Dimensions (HxWxD):* 21-11/16x25-15/16x10-3/4  
*Net Weight (lbs):* 68

*Compressor Type:* Inverter  
*Capacity Control Range (%):* \_\_\_\_\_  
*Airflow Rate (CFM):* 921  
*Gas Pipe Connection (inch):* 3/8  
*Liquid Pipe Connection (inch):* 1/4  
*Sound Pressure Level (dBA):* 48  
*Sound Power Level (dBA):* 62

### System Details

*Refrigerant Type:* R-410A  
*Holding Refrigerant Charge (lbs):* 2.2  
*Additional Charge (oz/ft):* 0.22  
*Pre-charge Piping (Length ft):* 33 ft  
*Max. Pipe Length (Total ft):* 65.6 ft

*Max. Pipe Length (Vertical ft):* 49.2 ft  
*Cooling Operation Range (°F):* 14 - 115  
*Cooling Range w/Baffle (°F):* 0 - 115  
*Heating Operation Range (°F):* 5 - 77  
*Heating Range w/Baffle (°F):* N/A

Project Name: \_\_\_\_\_  
Location: \_\_\_\_\_  
Engineer: \_\_\_\_\_  
Submitted to: \_\_\_\_\_  
Submitted by: \_\_\_\_\_  
Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
Date: \_\_\_\_\_  
Construction: \_\_\_\_\_  
Unit #: \_\_\_\_\_  
Drawing #: \_\_\_\_\_

**FTXN09KEVJU**

**RXN09KEVJU**

**FTXN09KEVJU**

Std U.S. Warranty: 6yrs Compressor, 2yrs Parts

**RXN09KEVJU**

Std U.S. Warranty: 6yrs Compressor, 2yrs Parts